**Page:** 1 Compilation date: 23/01/2012 Revision No: 1

#### Section 1: Identification of the substance/mixture and of the

#### 1.1. Product identifier

#### Product name: RX800F/NC

1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Logic RC Ltd 12-18 Hartham Lane
Hertford
Herfordshire

SG14 1QN United Kingdom Tel: +44(0)1992 558 226 Fax: +44(0)1992 554 032 Email: email@LogicRC.com

## **1.4. Emergency telephone number**

Emergency tel: +44(0)1992 558 226 (office hours only)

# Section 2: Hazards identification

Classification under CHIP:	Xi: R36/38; Sens.: R43; N: R51/53
Classification under CLP:	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317
Most important adverse effects:	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic
	organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

Label elements under CLP:	
Hazard statements:	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H411: Toxic to aquatic life with long lasting effects.
Signal words:	Warning
Hazard pictograms:	GHS07: Exclamation mark
	GHS09: Environmental



Precautionary statements: P264: Wash thoroughly after handling. P273: Avoid release to the environment. P280: Wear.

# SAFETY DATA SHEET

S-G11 Resin

		Page:	2
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove		
	contact lenses, if present and easy to do. Continue rinsing.		
	P321: Specific treatment (see on this label).		
	P332+313: If skin irritation occurs: Get medical.		
Label elements under CHIP:			
Hazard symbols:	Irritant.		
	Dangerous for the environment.		
	*		
Risk phrases:	R36/38: Irritating to eyes and skin.		
	R43: May cause sensitisation by skin contact.		
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the		
	aquatic environment.		
Safety phrases:	S2: Keep out of the reach of children.		
	S28: After contact with skin, wash immediately with plenty of water.		
	S37/39: Wear suitable gloves and eye / face protection.		
	S61: Avoid release to the environment. Refer to special instructions / safety data		
	sheets.		

#### 2.3. Other hazards

**PBT:** This substance is not identified as a PBT substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	>90%

# Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash		
	immediately with plenty of soap and water.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	stion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.		
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a		
	doctor.		
and and a second affection hat he and a second delayer d			

# 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

# SAFETY DATA SHEET

S-G11 Resin

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

# 5.1. Extinguishing media **Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. 5.2. Special hazards arising from the substance or mixture **Exposure hazards:** In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. 5.3. Advice for fire-fighters Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Section 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. 6.2. Environmental precautions Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. 6.3. Methods and material for containment and cleaning up Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. 6.4. Reference to other sections Section 7: Handling and storage 7.1. Precautions for safe handling Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. 7.2. Conditions for safe storage, including any incompatibilities Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. The floor of the storage room must be impermeable to prevent the escape of liquids. Suitable packaging: Must only be kept in original packaging. 7.3. Specific end use(s)

#### Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

#### 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must		
	be impermeable to prevent the escape of liquids.		
<b>Respiratory protection:</b>	Self-contained breathing apparatus must be available in case of emergency.		
Hand protection:	Protective gloves.		
Eye protection:	Safety glasses. Ensure eye bath is to hand.		
Skin protection:	Protective clothing.		
Environmental:	Ensure emissions from ventilation or equipment comply with environmental protection		
	legislation.		

# Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Yellow
Odour:	Perceptible odour
Viscosity:	Viscous
g point/range°C:	>200
Relative density:	1.17

Flash point°C: 245 pH: 7

9.2. Other information

Boiling

**Other information:** Not applicable.

#### Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

# 10.4. Conditions to avoid

## Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# **10.6.** Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

# Section 11: Toxicological information

#### 11.1. Information on toxicological effects

#### **Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Page: 4

		5-0111	Resili	
Sensitisation		DRM	Hazardous: calculated	Page:
Symptoms / routes of exposu				
			ess at the site of contact.	
			ess. The eyes may water profusely.	
			ess of the mouth and throat.	
	-		oat with a feeling of tightness in the chest.	Exposure
Section 12: Ecological inform	•	oughing or wheezing.		
12.1. Toxicity				
Ecotoxicity values:	••	ie.		
12.2. Persistence and degrad	lability			
Persistence and degradability:	Not biodegra	udable.		
12.3. Bioaccumulative potent	tial			
Bioaccumulative potential:	Bioaccumulat	tion potential.		
12.4. Mobility in soil				
Mobility:	Readily absor	rbed into soil.		
12.5. Results of PBT and vPvI	/B assessmer	nt		
PBT identification:	This substan	ce is not identified as	a PBT substance.	
12.6. Other adverse effects				
Other adverse effects:	Toxic to aqua	atic organisms. Toxic	to soil organisms.	
Section 13: Disposal conside	erations			
13.1. Waste treatment metho	ods			
Disposal operations:	Transfer to a	suitable container ar	nd arrange for collection by specialised disp	oosal
	company.			
Waste code number:	• •			
Disposal of packaging:		collection by specialise	ed disposal company.	
			he possible existence of regional or nationa	al
		regarding disposal.		
Section 14: Transport inform	nation			
14.1. UN number				
UN number:	UN3082			
14.2. UN proper shipping nan	me			
Shipping name:	ENVIRONME!	NTALLY HAZARDOUS	S SUBSTANCE, LIQUID, N.O.S. (BISPHENO	L A EPOXY
			· · ·	
	RESIN)			

# Transport class: 9

14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

# 14.6. Special precautions for user

#### Tunnel code: E

Transport category: 3

# Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

#### Section 16: Other information

#### **Other information**

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3:	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H411: Toxic to aquatic life with long lasting effects.
	R36/38: Irritating to eyes and skin.
	R43: May cause sensitisation by skin contact.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the
	aquatic environment.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any damage
	resulting from handling or from contact with the above product.