C-ARA8707 Talion 1/8 6S BLX Extreme Bash Speed Truggy 4WD RTR

ARRMA engineers have given the TALION 6S BLX Speed Truggy the Extreme Bash premium treatment! EX-B hardened components increase toughness everywhere it counts, resulting in a 1/8 scale speed basher with virtually unstoppable strength. It's also the first ARRMA EXB vehicle that comes ready-to-run with a Spektrum AVC radio and Spektrum 6S brushless power system — giving you the muscle and control to bash over brutal terrain at 70+ mph speeds.

Topped off with an exclusive EXB matte and gloss effect finished truck body and high downforce wing, the TALION 6S BLX Extreme Bash Speed Truggy represents the highest level yet of performance and durability in the 1/8 scale 6S BLX platform. For speed bashers who want the best, it's all right here.



FEATURES

- EXB anodised 7075 T6 aluminium laser etched parts included
- EXB Heavy Duty Turnbuckles
- EXB front bumper and skid plate
- EXB matte and gloss effect body
- EXB Heavy duty front upper steel hinge pins and mount
- EXB Anodised aluminium servo mount
- EXB Extra hard servo saver spring
- EXB Steel rear suspension mounts
- Spektrum DX3 Smart Transmitter with SR6110AT AVC Receiver
- Spektrum Firma 150A Smart ESC
- Spektrum Firma 4074 2050Kv Motor
- Spektrum S652 Steel Geared Servo
- Super-durable wheel hubs for increased strength
- Heavy-duty, all metal drivetrain
- Centre body support and aluminium centre brace for maximum durability
- Heavy-duty suspension arms
- Rubber-shielded bearings
- Steel spur gear
- Safe-D pinion and front/rear input cups
- ARRMA motor heatsink
- Large volume waterproof receiver box
- Belted multi-terrain dBoots Katar tyres

NEEDED TO COMPLETE

- 4S LiPo or 6S Hardcase LiPo Battery*
- Compatible Charger
- (4) AA Batteries
- LiPo Safe Charging Bag

IN THE BOX

- (1) ARRMA TALION 6S BLX Extreme Bash 1/8 Scale Speed Truggy RTR
- (1) Firma 150A Smart Waterproof ESC
- (1) Firma 4074 2050Kv Brushless Motor
- (1) 2.4GHz DX3 3-Channel Transmitter
- (1) SR6110AT AVC Receiver
- (1) SPMS652 Waterproof Metal-Geared Digital Servo
- (1) Product Manual

*Maximum battery dimensions 158x48x70mm. Minimum battery specs 5000mAh 50C.