



THE GEE BEE EXPERIENCE, REINVENTED

A-EFL020550 / A-EFL020575 Gee Bee R-2 1.0m BNF Basic with AS3X & SAFE Select / PNP

Gee Bee aircraft were among the pioneering racing airplanes that captivated just about everyone during aviation's Golden Age. Their cutting-edge, teardrop-shaped designs, coupled with small wings, required a skillful hand to fly well, but with the right pilot, they dominated the racecourse. The E-flite Gee Bee R-2 1.0m is a faithful replica of the iconic aircraft, featuring an abundance of scale detail along with modern features and technologies to deliver an unmatched flying experience. It assembles quickly and is sized to be easily stored and transported without disassembly. The Bind-N-Fly Basic version is equipped with enhanced AS3X+ technology that smooths out the effects of wind and turbulence like never before, plus optional-use SAFE Select technology that makes it easier to fly. Both versions include Spektrum digital, metal-gear servos, a 70A Smart Lite ESC, and a 4S-compatible motor.



FEATURES ☰

- A scale replica of the unique Golden Age icon with modern features and technologies, plus capabilities and performance
- Specially tuned motor compatible with popular 4S 3200-5000mAh batteries to deliver excellent performance and flight times
- 70-amp Spektrum Avian Smart Lite ESC provides real-time battery voltage, current, RPM, and other data via compatible receivers and transmitters
- Four factory-installed digital and metal-gear servos for precise and reliable control
- Fast and easy bolt-together assembly - no glue or special tools required
- Optional-use motor reversing for special ground handling and other capabilities
- Large and convenient top-mounted hatch provides easy access to the battery
- Fast and easy bolt-together assembly - no glue or special tools required

IN THE BOX ✓

- E-flite Gee Bee R-2 1.0m with:
- (1) Spektrum Brushless Outrunner Motor
- (1) Spektrum Digital, Metal-Gear Servos
- (4) Spektrum Avian 70-Amp Smart Lite Brushless ESC
- (1) Spektrum AR631+ 6-Channel Receiver with AS3X+ and SAFE Select*
- (1) Product Manual

NEEDED TO COMPLETE +

BNF Basic

- (1) Full-range 4-5+ channel Spektrum DSMX/DSM2 compatible transmitter

PNP

- (1) Full-range 4+ channel transmitter and receiver

Both

- (1) 4S 14.8V 3200-5000mAh LiPo with EC3 or IC3 Connector
- (1) Compatible LiPo charger