

COMPACT SIZE. FULL-SEND PERFORMANCE.



A-BLH01550 InFusion 210 BNF Basic with AS3X and SAFE

The Blade InFusion 210 combines compact size with exceptional durability, precision and performance. Its oversized direct-drive main motor delivers instant power with fewer moving parts, while extensive aluminium, metal and carbon-fibre construction provides strength and accurate control. Suitable for smooth hovering, sport flying and aggressive 3D aerobatics, it features an expertly tuned AR6250MHXF flybarless system with optional SAFE technology and AS3X stability. A brushless direct-drive tail motor keeps the helicopter firmly locked in, with an optional belt-drive conversion available for even greater tail authority. Spektrum Smart telemetry, metal-gear digital servos, 210mm blades and compatibility with popular 3S 850-1000mAh batteries complete this highly capable, factory-assembled mini helicopter.



FEATURES

- All-new, durable design for intermediate to experienced helicopter pilots
- Fully assembled, flight-tested and ready to fly
- Compact "mini" size for indoor and outdoor flying
- Oversized direct-drive main motor for instant power and fewer moving parts
- AS3X stabilisation for smooth, unrestricted flight performance
- Optional SAFE technology with angle limits and automatic self-levelling
- Strong carbon-fibre and aluminium airframe with an oversized tail boom
- Metal-gear digital cyclic servos for precise control
- Spektrum Smart telemetry for battery voltage, motor RPM and more
- Compatible with popular 3S 850-1000mAh LiPo batteries
- Optional belt-drive tail conversion for enhanced tail performance
- Customisable with alternative canopies and coloured aluminium parts

IN THE BOX

- Blade InFusion 210 with:
- (1) Brushless Outrunner Tail Motor
- (1) Brushless Outrunner Main Motor
- (3) Spektrum Digital, MG Servos
- (1) Spektrum AR6250MHXF Flybarless Flight Controller and (1) Receiver
- (1) Spektrum Dual 15A Main and 8A Tail Brushless Smart Lite ESC
- (1) Main Blade Holder
- (1) Product Manual

NEEDED TO COMPLETE

- Full-range 6-7+ channel Spektrum DSMX compatible transmitter
- 3S 11.1V 850-1000mAh LiPo battery with IC2 connector (or use a suitable IC2 adapter, sold separately)
- Compatible LiPo charger (plus a suitable IC2 adapter/charge lead, including SPMXCA320 or SPMXCA532, sold separately)